

A-8



Interior



Layer up to 2 mm



Application with a Roller



Working Temperature
-40°C
+10°C
+40°C



Total Drying Time
4 h

Ready Mixed Fine Finish White

Application

ŚMIG A-8 is intended for smoothing walls and ceilings indoors. It creates a permanent substrate for paints and wallpapers. The product can be used on all mineral construction substrates including wood-based and deformable surfaces and old paint coats on a permanent, clean, and dry substrate. It has the consistency of a paste. The product can be applied directly from

the bucket with a paint roller or traditional tools. Spread in layers of 1 to 2 mm. If applied with a paint roller, smoothen the wet surface with a flexible smoothing blade. This eliminates the dry sanding stage. When applied with traditional methods, use a 180–240 sanding sponge to smoothen the surface. Apply at ambient and substrate temperature of +10 to +40°C.

Packaging, Storage and Guarantees

The product is packed in recyclable plastic buckets with plastic handles and closed with a lid with a lock. ATTENTION: Store and transport the product at 0 to +40°C. Storage or transport under unfavourable conditions may cause delamination or granulation of the compound. In this case, the compound retains its properties as regards standard compliance, but for work

convenience it is necessary to mix it before use. Seal the bucket tightly, if the product is to be used again. The manufacturer guarantees product characteristics as per the standard within 12 months after the production date on the packaging as long as it is used as intended, described above, and in accordance to general construction practice.

Technical Data

Declaration of Performance:
Temperature of application:
Consumption with 1 mm layer:

EN 16566:2014
from +10 to +40°C
approx. 2 kg/m²

Drying time with 1 mm layer and +20°C:
Maximum single layer thickness:

approx. 4 h
2 mm