



Colorless  
(Dry)



Working  
Temperature



Interior &  
Exterior



Total Drying  
Time



Coverage

# K-15



## Universal Primer

ŚMIG K-15 Universal Primer is a top-class primer emulsion. It is a ready mix that does not need to be diluted. It can be applied on any mineral surface, including walls, ceilings and floors, both indoors and outdoors. The product is designed to improve adhesion of mortar, wall tile adhesive, self-leveling underlayment and paint coating. It is an excellent primer for acrylic and latex coatings that are water-based polymer resin dispersions, unless the paint manufacturer recommends

otherwise. The emulsion should not be applied as a primer for silica coatings. The primer should be applied using a roller or a spray gun. You can continue work after primer dries. In the case of surfaces of high absorption properties, it is permitted to dilute the primer with water in the ratio of 2:1. If the primer is used solely for dust suppression, it can be diluted in the ratio of 1:1. Minimum application temp. is +10°C.

### Application

The product is packed in recyclable plastic canisters. **ATTENTION:** Store and transport the product at 0 to +40°C. The manufacturer guarantees product characteristics as per

the standard within 12 months after the production date on the packaging as long as it is used as intended, described above, and in accordance to general construction practice.

### Packaging, Storage and Guarantees

### Technical Data

Polymer dispersion:

15%

Application rate:

approx. 0.2 l/m<sup>2</sup>

Temperature of application:

from +10 to +30°C

Drying time with 0,2 l/m layer and +20°C:

approx. 1.5 h